



15° vds

<b>1625/1715</b> Canopy / Kabine	Transportgewicht kg	Transport weight kg	Poids de transport kg	Peso de transporte kg	Peso di trasporto kg	<b>1850/1940</b> Canopy / Kabine
<b>1782/1872</b> Canopy / Kabine	Betriebsgewicht (Kabine) kg	Operating Weight (Cab) kg	Poids en charge (Cabine) kg	Peso di esercizio (Cabina) kg	Peso en orden de marcha, (Cabina) kg	<b>2004/2094</b> Canopy / Kabine
<b>13,2/17,9</b>	Schwungradleistung nach ISO, kW/PS	Performance to ISO, kW/HP	Performance au volant, kW/CV	Resa al volante ISO kW/CV	Potencia instalada kW/CV	<b>13,2/17,9</b>
<b>2185</b>	Grabtiefe mm	Digging depth mm	Profondeur d'excavation, mm	Profundidad de excavation, mm	Profondità di scavo, mm	<b>2500/2639*</b>
<b>2545</b>	max. Ausschütt- höhe, mm	max. Dumping hight, mm	Hauteur max. de déversement, mm	Altezza massima di versamento, mm	Altura máx. de descarga, mm	<b>2760</b>
<b>3867</b>	Grabradius mm	dumping radius mm	Rayon d'excavation mm	Raggio di scavo mm	Radio de excavacion mm	<b>4090</b>
<b>3810/990</b> <b>2380</b>	Länge/Breite/ Höhe, mm	Length/Width/ Height, mm	Longueur/Largeur/ Hauteur, mm	Largo/Ancho/ Altura total, mm	Lunghezza/Larghezza/ Altezza, mm	<b>3990/990</b> <b>2375</b>
-	Oberwagen- kipfung, (°)	tiltable (°)	basculement du châssis tournant, (°)	basculamiento del equipo giratorio, (°)	angolo di - flessione, (°)	<b>(15°)<sup>2</sup></b>

\* Löffelstiel lang (Option)  
Long dipperstick (option)  
Balancier long (optionnel)  
Balancin largo (opcional)  
Penetratore lungo (opzione)

<sup>2</sup> Option  
option  
optionnel  
opcional  
opzione



**WACKER  
NEUSON**